

RETREAD SPECIFICATIONS

The specs listed below are a recommendation only. Buffing equipment can vary and, as such, the specs below should be verified for each different style of buffer. Buff profile should be verified using pilot skives of 3/32" across buffed tread surface.

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	
11R22.5	BFL56	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
11R22.5	BTL66	660.0	26.0	210.0	8.27	8.25
11R24.5		660.0	26.0	210.0	8.27	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	210.0	8.27	8.25
11R22.5	BTL67	1321.0	52.0	225.0	8.86	8.25
11R24.5		1321.0	52.0	225.0	8.86	8.25
295/75R22.5		813.0	32.0	225.0	8.86	9.00
285/75R24.5		813.0	32.0	225.0	8.86	8.25
215/75R17.5	BAR26	559.0	22.0	160.0	6.30	6.00
235/75R17.5		660.0	26.0	180.0	7.09	6.75
225/70R19.5		711.0	28.0	180.0	7.09	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
215/75R17.5	BAR26SP	559.0	22.0	175.0	6.89	6.00
225/70R19.5		711.0	28.0	185.0	7.28	6.75
245/70R19.5		711.0	28.0	225.0	8.86	7.50
10R22.5	BDR77	610.0	24.0	200.0	7.87	7.50
11R22.5		660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
11R22.5	BDM90	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
11R22.5	BDL71	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
11R22.5	BDL81	1016.0	40.0	225.0	8.86	8.25
11R24.5		1016.0	40.0	225.0	8.86	8.25
295/75R22.5		660.0	26.0	225.0	8.86	9.00
285/75R24.5		813.0	32.0	225.0	8.86	8.25
11R22.5	BDL71W	711.0	28.0	240.0	9.45	8.25
11R24.5		711.0	28.0	240.0	9.45	8.25
295/75R22.5		762.0	30.0	240.0	9.45	9.00
285/75R24.5		762.0	30.0	240.0	9.45	8.25

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	
11R22.5	BAR02	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
315/80R22.5		762.0	30.0	230.0	9.06	9.00
11R22.5	BFR55	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
11R22.5	BFR57	1310.0	51.6	220.0	8.66	8.25
11R24.5		1310.0	51.6	220.0	8.66	8.25
295/75R22.5		735.0	28.9	220.0	8.66	9.00
285/75R24.5		797.0	31.4	220.0	8.66	8.25
12R22.5	BFR65	610.0	24.0	230.0	9.06	8.25
295/80R22.5		660.0	26.0	220.0	8.66	9.00
315/80R22.5		762.0	30.0	240.0	9.45	9.00
11R22.5	BDW63	711.0	28.0	235.0	9.25	8.25
11R24.5		711.0	28.0	235.0	9.25	8.25
11R22.5	BDW72	711.0	28.0	235.0	9.25	8.25
11R24.5		711.0	28.0	235.0	9.25	8.25
11R22.5	BD089	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
385/65R22.5	BAM99	1067.0	42.0	310.0	12.20	11.75
425/65R22.5		1067.0	42.0	330.0	12.99	12.25
385/65R22.5	BTR60	1067.0	42.0	315.0	12.40	11.75
225/70R19.5	BDR28/	813.0	32.0	190.0	7.48	6.75
245/70R19.5	BDR28SP	711.0	28.0	200.0	7.87	7.50
11R22.5	BAM01	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
11R22.5	BTR03	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	210.0	8.27	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
445/50R22.5	BTL63	1245.0	49.0	400.0	15.75	14.00
445/50R22.5	BDL73	1245.0	49.0	400.0	15.75	14.00
12.00R24	BD066	711.0	28.0	240.0	9.45	8.50
12.00R24	BDM19	711.0	28.0	240.0	9.45	8.50